

MAXI COBRA 14

øl 4mm fibreglass rod 80m - 200m lengths

ered in the second seco

Ritelite's Maxi Cobra conduit duct rodding systems provide a robust, compact, labour saving solution when installing cables in ducts, threading draw ropes through pipes or surveying drains with CCTV cameras.

Our high quality, fibreglass rod has a radially reinforced construction, is PP coated and spooled onto robust zinc plated steel frames with in-built parking brake. Total overall dimensions W 1050mm x H 1180mm x D 530mm.



Key Features



ROBUST Robust, zinc plated

steel frames



WHEELS Wheels for ease of manoeuvrability



SAFETY BRAKE Integral fully adjustable brake system fitted as standard

Standard System Lengths

PRODUCT CODE	DIAMETER	LENGTH	WEIGHT
MAXCO80C14	l4mm	80m	43.38Kg
MAXCO100C14	l4mm	100m	47.97Kg
MAXCO120C14	l4mm	120m	52.56Kg
MAXCO150C14	l4mm	150m	59.46Kg
MAXCO200C14	l4mm	200m	70.94Kg
Other lengths available on request			

Other lengths available on request.



Spares & Accessories



Guide tip for 14mm rod



End fitting for 14mm rod

MAXCOFLE/SP




Rod guiding eye



Replacement I I mm rod at a length of your choice



Maxi Cobra replacement frame and reel





Roller guide tip



Sonde adaptor MI2 to MI0 female



Accessory kit including various



Sonde 33kHz 38mm (requires MAXCOAD/911 to fit)



Splice repair kit for repairing broken rod



Replacement end fitting repair kit

fittings for additional functionality



Scan the QR code to view the full range of Maxi 14mm accessories



UK Enquiries +44 (0) 1780 758585 | Non UK Enquiries +44 (0) 1780 758582 E-mail: sales@cobraductrods.com | Web: www.cobraductrods.com